



RECTORSEAL T PLUS 2

Pipe Thread Sealant with PTFE

90/42 16th Floor, Sathorn Thani Bldg., North Sathorn, Silom, Bangrak, Bangkok 10500
Tel: (66)2-863-3200 Fax: (66)2-863-4955 www.egispro.com

DESCRIPTION:

RectorSeal T Plus 2 is a non-hardening thread sealant containing PTFE **plus** synthetic fibers. These fibers dispersed in a resinous base combined with inert mineral fillers provide maximum sealing performance. Its low coefficient of friction allows tighter joint makeup with lower torque. It also breaks out easily without galling, seizing, or damaging threads. It is excellent for service where immediate pressurization is necessary. RectorSeal T Plus 2 is non-toxic in accordance with NSF Standard 61. In addition, it is approved and listed with the Canadian Standards Association (CSA).

CHARACTERISTICS:

- PTFE enriched
- Allows immediate pressurization
- For use with potable water (hot or cold)
- Non-setting and will not dry out in the can
- Formulated for plastic and metal pipe
- Smooth easy application
- Non-flammable
- Non-staining and non-separating
- Lubricates and protects threads
- Low odor
- Lead free and contains no other metals
- For pressures up to 10,000 psi (liquids) and 2,000 psi (gases)
- Multipurpose

APPLICATIONS:

RectorSeal T Plus 2 can be used on a variety of metal and plastic piping including iron, galvanized steel, stainless steel, brass, copper, aluminum, polyethylene, reinforced fiberglass, PVC, ABS and CPVC including Flow Guard Gold



RECTORSEAL T PLUS 2

Pipe Thread Sealant with PTFE

90/42 16th Floor, Sathorn Thani Bldg., North Sathorn, Silom, Bangrak, Bangkok 10500
Tel: (66)2-863-3200 Fax: (66)2-863-4955 www.egispro.com

RectorSeal T Plus 2 is recommended for pipe carrying:

- Acids, Dilute
 - Air, Compressed
 - Ammonia- Gaseous, Liquid
 - Aliphatic Solvents
 - Caustic, Dilute
 - Cutting Oils (Low Aromatic)
 - Freons
 - Mineral Oils
 - Heating Oils
 - Helium, Gaseous
 - Hydraulic Oils
 - Hydrogen, Gaseous
 - Inert Gases, Gaseous
 - Kerosene
 - Liquefied Petroleum Gases (Butane, Propane, Mixtures)
 - Natural Gas
 - Nitrogen, Gaseous
 - Soap, Liquid
 - Vegetable Oils
 - Water (Hot or Cold)
- Not recommended for oxygen.

INSTRUCTIONS:

1. Stir before using.
2. Wipe threads clean.
3. For pipe diameters up to 1 1/4", apply to male threads only. For larger sizes, apply to both male and female threads.
4. Join pipe per ANSI Standards. Piping may be placed into service immediately.



RECTORSEAL T PLUS 2

Pipe Thread Sealant with PTFE

90/42 16th Floor, Sathorn Thani Bldg., North Sathorn, Silom, Bangrak, Bangkok 10500
Tel: (66)2-863-3200 Fax: (66)2-863-4955 www.egispro.com

PRECAUTIONS: FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT

PRECAUTIONS: Do not take internally. Do not burn - fumes may be harmful. Wash after handling.

FIRST AID: For any overexposure, get immediate medical attention after first aid is given.

Eyes - Flush 15 minutes with clean water.

Skin - Wash with soap and water.

Inhalation for burning fumes - Remove to fresh air.

Ingestion - Only if conscious, give large amounts of water and INDUCE VOMITING. Obtain medical attention.

FIRE AND SPILLS: For fire, use water fog, CO₂, foam, or dry chemicals. Wipe up spills to prevent footing hazard.

STORAGE AND HANDLING: Keep container closed when not in use. Do not reuse empty container.

KEEP OUT OF REACH OF CHILDREN. For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS:

Wt/Gal @ 77 degree F	11.0 +- .5 lbs/gal.
Flash Point SETA CC	Greater than 300 degree F
Non-volatiles	100%
Color	White
Shelf Life	2 years minimum
Federal Specification	TT-S-1732